

Fujitsu recommends Windows® 7.

Data Sheet

Fujitsu CELSIUS R670 Workstation

The New Uncompromising High-end Workstation

If you need record-breaking workstation performance, the ultra-reliable Fujitsu CELSIUS R670 with leading benchmark results will surpass all your expectations. This high-end dual processor workstation is individually configurable for the most power hungry, 24/7 operating environments. Best-in-class noise emissions of just 23 dB, and comprehensive ISV certifications that ensure smooth application operation, enhance your productivity.

Performance

Higher productivity

- High performance multi-core processors, hard disk drives and next generation graphics subsystems

Ergonomics

Quiet system for a pleasant working environment

- Optimized thermal management, low-noise chassis and silent fans

Reliability

System stability for the complete lifecycle

- High product standards thanks to top-quality components and comprehensive testing in certified in-house laboratories for 24/7 operation

Certification of workstation applications





Stability, compatibility and performance for the main workstation applications

- Comprehensive support for ISV applications and ease of integration into existing IT networks

Expandability

Excellent expandability for future demands

- Increased memory capacities of up to 192 GB



Components

Processor	Intel® Xeon® processor X5690 (6 Cores / 12 Threads, 3.46 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5687 (4 Cores / 8 Threads, 3.60 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5680 (6 Cores / 12 Threads, 3.33 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5677 (4 Cores / 8 Threads, 3.46 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5675 (6 Cores / 12 Threads, 3.06 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5672 (4 Cores / 8 Threads, 3.20 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5670 (6 Cores / 12 Threads, 2.93 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5667 (4 Cores / 8 Threads, 3.06 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5660 (6 Cores / 12 Threads, 2.80 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5650 (6 Cores / 12 Threads, 2.66 GHz, 12 MB, 6.4 GT/s)
	Intel® Xeon® processor X5647 (4 Cores / 8 Threads, 2.93 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5640 (6 Cores / 12 Threads, 2.26 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5630 (4 Cores / 8 Threads, 2.13 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor L5609 (4 Cores / 8 Threads, 1.86 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5649 (6 Cores / 12 Threads, 2.53 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5645 (6 Cores / 12 Threads, 2.40 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5640 (4 Cores / 8 Threads, 2.66 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5630 (4 Cores / 8 Threads, 2.53 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5620 (4 Cores / 8 Threads, 2.40 GHz, 12 MB, 5.86 GT/s)
	Intel® Xeon® processor E5607 (4 Cores / 8 Threads, 2.26 GHz, 8 MB, 4.8 GT/s)
Intel® Xeon® processor E5606 (4 Cores / 8 Threads, 2.13 GHz, 8 MB, 4.8 GT/s)	
Intel® Xeon® processor E5603 (4 Cores / 8 Threads, 1.60 GHz, 8 MB, 4.8 GT/s)	
Operating systems	
Operating system	Windows® 7 Professional 64-bit
	Windows® 7 Professional 32-bit
Operating system compatible	Windows® XP Professional x64 Edition Windows® XP Professional Linux
Operating system notes	Red Hat® certification Novell® certification For some configurations third party drivers are currently not available or configuration restrictions may apply.
Memory modules	
	1 GB (1 module(s) 1 GB) DDR3, 1333 MHz, PC3-10600
	1 GB (1 module(s) 1 GB) DDR3, ECC, 1333 MHz, PC3-10600
	2 GB (1 module(s) 2 GB) DDR3, ECC, 1333 MHz, PC3-10600
	2 GB (1 module(s) 2 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
	4 GB (1 module(s) 4 GB) DDR3, ECC, 1333 MHz, PC3-10600
	4 GB (1 module(s) 4 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
	8 GB (1 module(s) 8 GB) DDR3, registered, ECC, 1333 MHz, PC3-10600
	16 GB (1 module(s) 16 GB) DDR3, registered, ECC, 1066 MHz, PC3-8500

Graphics add on cards (optional)	Ultra-high-end 3D: NVIDIA® Quadro® 6000, 6 GB, 448 cores, PCIe x16, 1x DVI-I, 2x DisplayPort, 2x DVI/VGA Ultra-high-end 3D: NVIDIA® Quadro® 5000, 2.5 GB, 352 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort, DVI, VGA High-end 3D: AMD FirePro™ V7900, 2 GB, 1140 stream processors, PCIe x16, 4 x DisplayPort High-end 3D: NVIDIA® Quadro® 4000, 2 GB, 256 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort Midrange 3D: NVIDIA® Quadro® 2000D, 1 GB, 192 cores, PCIe x16, 2x Dual Link DVI-I Midrange 3D: NVIDIA® Quadro® 2000, 1 GB, 192 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort Midrange 3D: AMD FirePro™ V5900, 2 GB, 800 stream processors, PCIe x16, Dual Link DVI-I, 2x DisplayPort Entry 3D: AMD FirePro™ V4900, 1 GB, 480 stream processors, PCIe x16, Dual Link DVI-I, 2x DisplayPort Entry 3D: NVIDIA® Quadro® 600, 1 GB, 96 cores, PCIe x16, Dual Link DVI-I, DisplayPort Entry 3D: NVIDIA® Quadro® 400, 512 MB, 48 cores, PCIe x16, 1x DVI-I, DisplayPort Entry 3D: ATI FirePro™ V3800, 512 MB, 400 stream processors, PCIe x16, Dual Link DVI-I, DisplayPort Professional 2D: NVIDIA® Quadro® NVS 450, 512 MB, 2 x 8 cores, PCIe x16, 4 x DisplayPort Professional 2D: NVIDIA® Quadro® NVS 300, 512 MB, 16 cores, PCIe Gen2 x16, 2x DVI/VGA Professional 2D: NVIDIA® Quadro® NVS 295, 256 MB, 8 Cores, PCIe x16, 2x DisplayPort Multi monitor 2D: NVIDIA® Quadro® NVS 295, 256 MB, 8 Cores, PCIe x1, 2x DisplayPort Remote Graphics: CELSIUS RemoteAccess Card, PCIe x1, 2x DVI-I, PCoIP GPU computing card: NVIDIA® Tesla™ C2075, 6 GB, 448 cores, PCIe x16, 1x DVI-I
Hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch SSD SATA, 256 GB, 2.5-inch SSD SATA, 128 GB, 2.5-inch HDD SATA III, 10000 rpm, 600 GB, 3.5-inch HDD SATA III, 10000 rpm, 300 GB, 3.5-inch HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch, business critical HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical HDD SATA II, 7200 rpm, 2000 GB, 3.5-inch, business critical HDD SATA II, 7200 rpm, 160 GB, 3.5-inch, S.M.A.R.T. HDD SAS, 15000 rpm, 600 GB, 3.5-inch internal HDD SAS, 15000 rpm, 450 GB, 3.5-inch HDD SAS, 15000 rpm, 300 GB, 3.5-inch
Hard disk notes	2.5-inch drives will be mounted in the 3.5-inch bays One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.
Drives (optional)	Blu-ray Disc™ Triple Writer DVD-ROM DVD Super Multi MultiCard Reader 20in1, 5.25-Inch MultiCard Reader 20in1 USB 2.0 5.25-Inch
Interface add on cards/components (optional)	WLAN III, 802.11g/Draft-n (Windows only) USB 3.0 PCIe x1 Gigabit Ethernet PCIe x1 eSATA Interface Dual serial card PCIe x1, powered Dual serial card PCIe x1 Dual 1 Gigabit Ethernet PCIe x4 Dual 10 Gigabit Ethernet PCIe x8
Interface add on/component note	1x eSATA interface already on board
Base unit	CELSIUS R670-2
Mainboard	
Mainboard type	D2618

Mainboard

Formfactor	AT03
Chipset	Intel® 5520, Intel® 82801JIB ICH10
Processor socket	LGA 1366
Processor quantity maximum	2
Memory slots	12 (6 per processor)
Supported capacity RAM (max.)	192 GB
Memory notes	In configurations with 4 GB and more the visible memory may be reduced to approximately 3.5 GB or less (for 32-bit operating systems) and configurations with 8 GB the visible memory may be reduced to approximately 7.5 GB or less (depending on system configuration).
LAN	2x Built-in 10/100/1000 MBit/s Realtek RTL8111
Audio codec	Realtek ALC663
Audio features	High Definition Audio

I/O controller on board

Serial ATA total	4
SATA RAID support	0, 1, 1E
SAS Controller type	8 ports, LSI 1068E
SAS RAID support	0, 1, 1E

Interfaces

Audio: in (rear)	1
Audio: out / SPDIF (rear)	2 / 1
Audio: in	1
Audio: out	1
FireWire (IEEE1394) (front)	1
FireWire (IEEE1394) (rear)	1
Internal speakers	1
USB 2.0 total	11
USB front	2
USB rear	6
USB internal	3, thereof 1 type A
Serial (RS-232)	1 (9 pin)
Mouse / Keyboard (PS/2)	1 / 1
Ethernet (RJ-45)	2
eSATA	1
Interface Module notes	Anytime USB charge functionality

Drive bays

Drive bays total	7
3.5-inch internal bays	4
5.25-inch external bays	3

Slots

PCI-Express 2.0 x16	2 x (350 mm /) Full height
PCI-Express 2.0 x4 (mech. x8)	3 x (350 mm) Full height
PCI (32-bit / 33 MHz)	1 x (350 mm /) Full height

Graphics

Graphics notes	For some configurations third party drivers are currently not available or configuration restrictions may apply.
----------------	--

Electrical values

Operating voltage range	100 V - 240 V
Operating line frequency range	50 Hz - 60 Hz
Max. output of single power supply	1000 W up to 85% efficiency

Noise for standard configuration (HDD, ODD, FDD)

Noise Operation mode 4: High load	23 dB(A)
-----------------------------------	----------

Noise for standard configuration (HDD, ODD, FDD)

Idle mode	22 dB(A)
Office mode	23 dB(A)
Noise notes / description	depending on configuration

Dimensions / Weight / Environmental

Dimensions (W x D x H)	215 x 622 x 446 mm
Weight	26 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	15 - 35°C
Operating relative humidity	10 - 75 %

Compliance

Product	CELSIUS R670-2
Model	MCL-D2618
Germany	GS depending on configuration
Europe	CE
USA/Canada	cCSAus FCC Class B
Global	RoHS (EU & China) ENERGY STAR® 5.0 Medical EMC standard IEC60601-1-2 in combination with medical kit
China	CCC
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/

Security

System protection	Kensington Lock support Eye for padlock Optional: Integrated cabinet lock Seal option
Audit proof protection	Write protect option for the Flash EPROM Boot protection for floppy disk / CD drive and write protection for floppy disk drive Dynamic USB security for full hardware USB protection Control of all USB interfaces External USB interfaces detachable separately Embedded security (TPM 1.2) - Infineon
Access protection	Optional: Access protection via internal SmartCard reader User and supervisor BIOS password Optional: SmartCase Logon+

Additional Software

Additional software (preinstalled)	Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Windows® 7, Windows® Vista and Windows® XP CyberLink PowerDVD 9 Nero 9 Essentials XL Recovery DVD (Windows® 7)

Manageability

Manageability technology	DeskUpdate Driver management
Manageability software	DeskView 10.x client management including: DASH 1.1 remote system management

Manageability

DeskView components	<ul style="list-style-type: none"> On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration
----------------------------	---

Supported standards	<ul style="list-style-type: none"> WMI BootP (made4you) PXE WoL (Wake on LAN)
----------------------------	---

Manageability link	http://ts.fujitsu.com/manageability
---------------------------	---

Input device / components

Input devices (optional)	<ul style="list-style-type: none"> Optical USB tilt wheel mouse Keyboard Optical USB/PS2 tilt wheel mouse Space Navigator USB Space Explorer USB Space Pilot USB
---------------------------------	--

Warranty

Standard Warranty	3 years (depending on country)
Service level	On-site Service (depending on country)

Maintenance and Support Services - the perfect extension

Recommended Service	5x9, Response Time: Next Business Day
Service Weblink	http://www.fujitsu.com/fts/services/support

More information

Fujitsu platform solutions

In addition to Fujitsu CELSIUS R670, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS R670, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-06-01 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions