


ThinkCentre M93/M93p SFF Pro Platform Specifications

Product Specifications Reference (PSREF)

Processor	4th Generation Intel® Core™ i3 / i5 / i7 Processors	Manageability	Intel Active Management Technology 9.0 (Intel AMT 9.0)																																				
	<table border="1"> <thead> <tr> <th>Processor</th> <th>Cores / Threads</th> <th>Frequency (Base/Max)</th> <th>Cache</th> <th>Memory Types</th> <th>Integrated Graphics</th> </tr> </thead> <tbody> <tr> <td>Core i5-4670</td> <td>4 / 4</td> <td>3.4 GHz / 3.8 GHz</td> <td>6 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i5-4570</td> <td>4 / 4</td> <td>3.2 GHz / 3.6 GHz</td> <td>6 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i5-4590</td> <td>4 / 4</td> <td>3.3 GHz / 3.7 GHz</td> <td>6 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i7-4770</td> <td>4 / 8</td> <td>3.4 GHz / 3.9 GHz</td> <td>8 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> <tr> <td>Core i7-4790</td> <td>4 / 8</td> <td>3.6 GHz / 4 GHz</td> <td>8 MB</td> <td>DDR3-1600</td> <td>HD 4600</td> </tr> </tbody> </table>	Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Integrated Graphics	Core i5-4670	4 / 4	3.4 GHz / 3.8 GHz	6 MB	DDR3-1600	HD 4600	Core i5-4570	4 / 4	3.2 GHz / 3.6 GHz	6 MB	DDR3-1600	HD 4600	Core i5-4590	4 / 4	3.3 GHz / 3.7 GHz	6 MB	DDR3-1600	HD 4600	Core i7-4770	4 / 8	3.4 GHz / 3.9 GHz	8 MB	DDR3-1600	HD 4600	Core i7-4790	4 / 8	3.6 GHz / 4 GHz	8 MB	DDR3-1600	HD 4600	Security chip	Trusted Platform Module, TCG 1.2-compliant
Processor	Cores / Threads	Frequency (Base/Max)	Cache	Memory Types	Integrated Graphics																																		
Core i5-4670	4 / 4	3.4 GHz / 3.8 GHz	6 MB	DDR3-1600	HD 4600																																		
Core i5-4570	4 / 4	3.2 GHz / 3.6 GHz	6 MB	DDR3-1600	HD 4600																																		
Core i5-4590	4 / 4	3.3 GHz / 3.7 GHz	6 MB	DDR3-1600	HD 4600																																		
Core i7-4770	4 / 8	3.4 GHz / 3.9 GHz	8 MB	DDR3-1600	HD 4600																																		
Core i7-4790	4 / 8	3.6 GHz / 4 GHz	8 MB	DDR3-1600	HD 4600																																		
		Security features	<ul style="list-style-type: none"> One lock to secure both cover and entire system to fixed object: <ul style="list-style-type: none"> -Padlock loop (in rear for opt padlock) -Security slot (in rear for optional Kensington® MicroSaver® cable) Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Optional Chassis intrusion switch 																																				
Memory	32GB max, UDIMM, PC3-12800 1600MHz DDR3, four 240-pin DIMM sockets	Keyboard	Preferred Pro USB Keyboard (USB connector), Lenovo logo																																				
Disk	<i>Some:</i> SATA 6.0Gb/s, 2.5" Wide, 7200 rpm <i>Some:</i> SATA 6.0Gb/s, 3.5" Wide, 7200 rpm <i>Some:</i> 500GB (5400 rpm, 2.5" wide) or 1TB (7200 rpm, 3.5" wide) hybrid hard disk / with 8GB MLC NAND flash memory, SATA 6.0Gb/s, 2.5" wide	Mouse	Enhanced Optical USB Mouse, black, Lenovo logo																																				
Optical	<i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Wide <i>Some:</i> DVD-ROM SATA 1.5Gb/s Drive	Mechanical	<ul style="list-style-type: none"> SFF Pro (12.9L), business black color; metal case (WxDxH) 13.31" X 14.76" X 4.02"; 338mm X 375mm X 102mm 17.20 lb (7.8 kg) in maximum configuration Toolless cover removal, adapter retention Toolless disk and optical drive removal Bay 1: 5.25", 1.6" high, external, std optical Bay 2: 3.5", 1" high, internal, std disk Bay 3: 2.5", N/A, internal, optional or come with opt 2.5" 2nd disk Bay 4: 3.5", 0.5" high, external, opt reader Slot 1: Low Profile, PCI Express 3.0 x16 (40w max) Slot 2: Low Profile, PCIe 2.0 x1 Slot 3: Low Profile, PCIe 2.0 x16 (x4 elec, 40w max) Slot 4: Low Profile, 32-bit PCI 2.3 																																				
Onboard SATA	<i>Some:</i> Super Multi-Burner DVD±RW SATA 1.5Gb/s Drive Two SATA cables (each 1-drop to device), three SATA 6.0Gb/s connectors, one eSATA connector (SATA 6.0Gb/s) Optional 29-in-1 media reader, internal USB 2.0	Floor Stand	Optional system floor stand for vertical orientation																																				
Media reader	Optional 29-in-1 media reader, internal USB 2.0	Power supply	240 watts, autosensing, 85% PSU																																				
Graphics	Intel HD Graphics 4400/4600 in processor, uses main memory, DirectX® 11, one VGA, two DisplayPort™, supports three independent displays, works along with discrete graphics to support five independent monitors; <i>Maximum resolution:</i> 2560x1600 (DisplayPort)@60Hz; 1920x1200 (VGA)@60Hz (Reduced Blanking) <i>Some:</i> AMD Radeon HD 8570 , DirectX 11, 3D Hardware Acceleration, 2GB, PCI Express 3.0 x16 adapter (8x elec), one VGA, one HDMI, 40 watts; <i>Max resolution:</i> 4096x2160 (HDMI)@24Hz; 2048x1536 (VGA)@85Hz <i>Some:</i> AMD Radeon™ HD 8470 , DirectX 11, 3D Hardware Acceleration, 512MB, PCI Express® 2.0 x16 adapter, one VGA, one DisplayPort, 25 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz <i>Some:</i> AMD Radeon™ HD 7450 , DirectX 11, 1GB, PCI Express 2.0 x16 adapter, one DVI-I (includes DVI-to-VGA dongle), one DisplayPort, 25 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort, DVI-I)@60Hz <i>Some:</i> NVIDIA® GeForce® GT 620 , DirectX 11, 3D Hardware Acceleration, 1GB, PCI Express 2.0 x16 adapter, one VGA, one DisplayPort, 30 watts; <i>Max resolution:</i> 2560x1600 (DisplayPort)@60Hz; 2048x1536 (VGA)@85Hz	Limited warranty ³	<i>Some:</i> 3-years, limited onsite service / service upgrades available <i>Some:</i> 3-years, limited onsite service, IWS (International Warranty Service ⁹) / service upgrades available For Lenovo service upgrade options, please go to S-TC sheet																																				
DP cable	None	Preload	Preloaded operating system <i>Some:</i> Windows® 7 Professional 32 <i>Some:</i> Windows 7 Professional 64 <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8 Pro 64-bit <i>Some:</i> Windows 7 Professional 64 preinstalled through downgrade rights in Windows 8.1 Pro 64-bit																																				
Chipset	Intel Q87 Chipset		Ready to install applications (only some listed) <ul style="list-style-type: none"> Rescue and Recovery™ Password Manager Preloaded applications (only some listed) <ul style="list-style-type: none"> ThinkVantage® Product Recovery ThinkVantage System Update ThinkVantage Communication Utility Desktop Power Manager View Management Utility Lenovo Cloud Storage by SugarSync Lenovo Solution Center Lenovo Message Center Plus Norton™ Internet Security (30 days of virus definitions) Adobe® Reader® Skype™ Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (DVD±RW, DVD) Cyberlink Power2Go (DVD±RW) Cyberlink PowerProducer (DVD±RW) Evernote Intel AppUp Intel Small Business Advantage Nitro Pro 																																				
Front ports	Two USB 3.0, two optional USB 2.0, microphone (stereo, 3.5mm), headphone (stereo, 3.5mm)	Environment	ENERGY STAR® 6.0 (Need 85% PSU and Windows OS); EPEAT™ Gold rating (Need 85% PSU and Windows OS); GREENGUARD®; RoHS-compliant; Cisco EnergyWise compatible; ULE Gold																																				
Rear ports	Four USB 3.0, two USB 2.0, serial (9-pin), optional 2nd serial (9-pin), optional parallel (25-pin), ethernet (RJ-45), one VGA, two DisplayPort, additional VGA, DisplayPort, or HDMI on optional graphic card on some models	Accessories	For compatible accessories, please go to TC-AQP sheet																																				
Rear audio ports	Line-in (stereo, 3.5mm), line-out (stereo, 3.5mm), microphone (stereo, 3.5mm)																																						
IEEE 1394	None																																						
Audio support	High Definition (HD) Audio, Realtek® ALC662 codec / internal speaker (1watt)																																						
WLAN ¹³	<i>Some:</i> 11b/g/n, PCIe Half Mini Card, Realtek RTL8723BE, Wi-Fi/BT 4.0, 1x1 <i>Some:</i> 11b/g/n, PCIe Half Mini Card, Intel Centrino® Wireless-N 105, 1x1 <i>Some:</i> 11b/g/n, PCIe Half Mini Card, Intel Centrino Wireless-N 2230, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11a/b/g/n, PCIe Half Mini Card, Intel Centrino Advanced-N 6235, Wi-Fi + Bluetooth combo adapter, 2x2 <i>Some:</i> 11b/g/n, PCIe Half Mini Card, Intel Wireless-N 7260, Wi-Fi/BT 4.0, 2x2 <i>Some:</i> 11ac/a/b/g/n, PCIe Half Mini Card, Intel Dual Band Wireless-AC 7260, Wi-Fi + BT combo adapter, 2x2																																						
Bluetooth™	<i>Some:</i> Bluetooth 4.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter																																						
Ethernet	One gigabit ethernet port, Intel I217-LM (Clarkville), Wake on LAN®																																						
Modem	None																																						

See footnotes for more detailed information