HP Z820 Workstation

Ultimate performance for ultimate projects.





Built for high-end computing and visualization.

The dual-processor HP Z820 Workstation delivers outstanding performance, award-winning industrial design, and tool-free serviceability in the industry's most expandable chassis. With next generation Intel® Xeon® processors, support for up to 16 processing cores, and the latest professional graphics, you'll tackle even the most demanding projects like never before.

Unmatched Design. Inside and Out.

With its expandable design, the HP Z820 Workstation gives you the confidence to produce your best work. Designed for a wide-range of needs, the HP Z820 offers enhanced tool-free access and unbelievable power at whisper-quiet levels. The result is unparalleled design power in a system that is sleek and uncluttered, inside and out.

Multitasking Made Easy.

The HP Z820 Workstation employs a variety of Intel® Xeon® E5-2600 processors^{1,2,3} that enable next generation PCI Express technology. With support for 2 processors, the HP Z820 can operate with up to 16 processing cores, delivering ultimate performance to help you accomplish more every minute. Featuring the Xeon® C600 series chipset, LSI SAS 2308 controller, and dual Quick Path Interconnects between the processors, the two work together to help you work more effectively than ever before.

Ultra-Powerful Visuals and High Performance Computing.

Built to support next generation PCIe Gen3 graphics from AMD and NVIDIA, the HP Z820 Workstation currently offers a wide range of cards from Pro 2D to ultra high-end 3D graphics to get the job done. With dual graphics processor support, the HP Z820 can drive up to 8 displays, giving you the power and space you need to multitask like a pro. Plus, get the highest performing GPU computing solutions available in the Z family, like NVIDIA's Maximus, on the HP Z820.









HP Z820 Workstation

	Hyper-Threading Y Y Y Y Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	K rpm SATA drives: 300 GB SFF FF, 3.6 TB max; Up to (5) 3.5-in	F, 1.5 TB max; Up to (6) 2.5-inch ich 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2687 3.1 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2680 2.9 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2680 2.7 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.7 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.6 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2667 2.6 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 3.18 10 MB 1060 MHz 4 Intel® Xeon® Processor E5-2609 3.18 30 MB	Y Y Y Y Y Y Y Y Y N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y	3, 7 4, 9 4, 8 4, 7 3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A	
Intel* Xeon* Processor E5-2687 3.1 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2690 2.9 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2680 2.7 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2667 2.6 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2667 2.9 15 MB 1600 MHz 8 Intel* Xeon* Processor E5-2667 2.9 15 MB 1600 MHz 8 Intel* Xeon* Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel* Xeon* Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel* Xeon* Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel* Xeon* Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel* Xeon* Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel* Xeon* Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel* Xeon* Processor E5-2609 2.5 Intel* Xeon* Processor E5-2609 2.5 Intel* Xeon* Processor E5-2609 2.6 Intel* Xe	Y Y Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y T O O O O	4, 9 4, 8 4, 7 3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s 5, 1.5 TB max; Up to (6) 2.5-inch (ch 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2690 2.9 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2680 2.7 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2670 2.6 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2667 2.9 15 MB 1600 MHz 6 Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 3.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 3.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 3.8 3.	Y Y Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y T O O O O	4, 9 4, 8 4, 7 3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A ed 8-channel SAS 6 Gb/s 7, 1.5 TB max; Up to (6) 2.5-inch (ch 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2680 2.7 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2670 2.6 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2667 2.9 15 MB 1600 MHz 6 Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.5 Intel® Xeon® Pro	Y Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y T O O O O	4, 8 4, 7 3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A	
Intel® Xeon® Processor E5-2667	Y Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y Y Y T D 0, 1, 5, 10 capable; Integrat	4, 7 3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A	
Intel® Xeon® Processor E5-2667 2.9 15 MB 1600 MHz 6 Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 1.8 10 MB 1066 MHz 10 MB 1066 MHz 10 MB 1066 MHz 10 MB 1066 MHz 10 MB	Y Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y Y Y Y T D 0, 1, 5, 10 capable; Integrat	3, 6 4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s	
Intel® Xeon® Processor E5-2665 2.4 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2620 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® C602 Chipset Memory⁵	Y Y Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y ID 0, 1, 5, 10 capable; Integrat IK rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	4, 7 5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A Sed 8-channel SAS 6 Gb/s	
Intel® Xeon® Processor E5-2660 2.2 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2600 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 10 MB 1066 MHz 10 MB 1066 MHz 10 MB 1066 MHz 10 MB	Y Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y Y Y Y Y T O O O O O O O O O	5, 8 4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s	
Intel® Xeon® Processor E5-2650 2.0 20 MB 1600 MHz 8 Intel® Xeon® Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 Int	Y Y Y Y N N N SATA 3 Gb/s controller, RAI	Y Y Y Y Y Y ID 0, 1, 5, 10 capable; Integrat	4, 8 1, 2 3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s	
Intel® Xeon® Processor E5-2643 3.3 10 MB 1600 MHz 4 Intel® Xeon® Processor E5-2640 2.5 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® C602 Chipset	Y Y Y N N PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	Y Y Y Y Y ID 0, 1, 5, 10 capable; Integrate K rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	1, 2 3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s F, 1.5 TB max; Up to (6) 2.5-inch ich 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® C602 Chipset 10 MB 1060 MHz, 4 channels per Integrated 2-channel SATA 6 Gb/s controller, RAID 0, 1 capable; Integrated 4-channel controller, RAID 0, 1, 10 capable; Optional LS19260-8i 8-port 6 Gb/s SAS HW RAID Storage 6.7	Y Y N N N PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	Y Y Y Y ID 0, 1, 5, 10 capable; Integrat IK rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	3, 5 3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s , 1.5 TB max; Up to (6) 2.5-inch ch 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2630 2.3 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2620 2.0 15 MB 1333 MHz 6 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Intel® C602 Chipset 10 MB 1060 MHz, 4 channels per Integrated 2-channel SATA 6 Gb/s controller, RAID 0, 1 capable; Integrated 4-channel controller, RAID 0, 1, 10 capable; Optional LS19260-8i 8-port 6 Gb/s SAS HW RAID Storage 6.7	Y N N PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	Y Y Y ID 0, 1, 5, 10 capable; Integrat IK rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	3, 5 3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s F, 1.5 TB max; Up to (6) 2.5-inch Ich 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2609 2.4 10 MB 1066 MHz 4 Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4 Chipset Intel® C602 Chipset	N N PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	Y Y ID 0, 1, 5, 10 capable; Integrat K rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	3, 5 N/A N/A N/A ed 8-channel SAS 6 Gb/s -, 1.5 TB max; Up to (6) 2.5-inch ch 15K rpm SAS drives: 300,	
Intel® Xeon® Processor E5-2603 1.8 10 MB 1066 MHz 4	N PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	Y ID 0, 1, 5, 10 capable; Integration (INT) INT (INT) IN	N/A ed 8-channel SAS 6 Gb/s =, 1.5 TB max; Up to (6) 2.5-inch ch 15K rpm SAS drives: 300,	
Chipset Intel® C602 Chipset Memorys 16 DIMM slots, up to 512 GB, 8-channel ECC DDR3, up to 1600 MHz, 4 channels per Integrated 2-channel SATA 6 Gb/s controller, RAID 0, 1 capable; Integrated 4-channel controller, RAID 0, 1, 10 capable; Optional LSI 9260-8i 8-port 6 Gb/s SAS HW RAID Storage®.7 Up to (5) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2 TB; Up to (4) 3 TB, 14 TE 10K rpm SATA drives: 250, 500, 1000 GB SFF, 6 TB max; Up to (6) 2.5-inch 10K rpm 450, 600 GB, 3 TB max; Up to (6) 2.5-inch SATA solid state drives: 128, 160, 256, 31 Up to (1) 3.5-inch SATA SED hard drive: 500 GB, 500 GB max Optical Storage®.9 DVD-ROM, DVD+/-RW Super-Multi and Slot-Load, Blu-ray Writer Drive Bays 3 external 5.25-inch bays, 4 internal 3.5-inch bays Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹⁰ Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 Mid-range 3D: NVIDIA Quadro 410, AMD FirePro¹™ V5900, NVIDIA Quadro 6 Mid-range 3D: NVIDIA Quadro 4000, AMD FirePro¹™ V5900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro¹™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro¹™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro¹™ V7900, NVIDIA Quadro Motor Mid-range 3D: NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro³™ V7900, NVIDIA Quadro 6 NVID	PU SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	ID 0, 1, 5, 10 capable; Integrat K rpm SATA drives: 300 GB SFI FF, 3.6 TB max; Up to (5) 3.5-in	ed 8-channel SAS 6 Gb/s -, 1.5 TB max; Up to (6) 2.5-inch ch 15K rpm SAS drives: 300,	
Memory⁵ 16 DIMM slots, up to 512 GB, 8-channel ECC DDR3, up to 1600 MHz, 4 channels per Drive Controllers Integrated 2-channel SATA 6 Gb/s controller, RAID 0, 1 capable; Integrated 4-channel controller, RAID 0, 1, 10 capable; Optional LSI 9260-8i 8-port 6 Gb/s SAS HW RAID Storage ^{6,7} Up to (5) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2 TB; Up to (4) 3 TB, 14 TE 10K rpm SATA drives: 250, 500, 1000 GB SFF, 6 TB max; Up to (6) 2.5-inch 10K rpm 450, 600 GB, 3 TB max; Up to (6) 2.5-inch SATA solid state drives: 128, 160, 256, 3 Up to (1) 3.5-inch SATA SED hard drive: 500 GB, 500 GB max Optical Storage ^{8,9} DVD-ROM, DVD+/-RW Super-Multi and Slot-Load, Blu-ray Writer Drive Bays 3 external 5.25-inch bays, 4 internal 3.5-inch bays Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen3 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹0 Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 Entry 3D: NVIDIA Quadro 410, AMD FirePro TM V3900, NVIDIA Quadro 6 MVIDIA Quadro 2000, AMD FirePro TM V7900, NVIDIA Quadro 6 MVIDIA Quadro 2000, AMD FirePro TM V7900, NVIDIA Quadro 6 MVIDIA Quadro 2000, AMD FirePro TM V7900, NVIDIA Quadro MOD, AMD FirePro TM V7900, NVIDIA QUAD MOD, AMD FirePro TM V7900, NVIDIA QUAD	SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	K rpm SATA drives: 300 GB SFF FF, 3.6 TB max; Up to (5) 3.5-in	F, 1.5 TB max; Up to (6) 2.5-inch ich 15K rpm SAS drives: 300,	
Drive Controllers Integrated 2-channel SATA 6 Gb/s controller, RAID 0, 1 capable; Integrated 4-channel controller, RAID 0, 1, 10 capable; Optional LSI 9260-8i 8-port 6 Gb/s SAS HW RAID Storage ^{6,7} Up to (5) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2 TB; Up to (4) 3 TB, 14 TE 10K rpm SATA drives: 250, 500, 1000 GB SFF, 6 TB max; Up to (6) 2.5-inch 10K rpm 450, 600 GB, 3 TB max; Up to (6) 2.5-inch SATA SGID state drives: 128, 160, 256, 31 Up to (1) 3.5-inch SATA SED hard drive: 500 GB, 500 GB max Optical Storage ^{8,9} DVD-ROM, DVD+/-RW Super-Multi and Slot-Load, Blu-ray Writer Drive Bays 3 external 5.25-inch bays, 4 internal 3.5-inch bays Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics ¹⁰ Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 Entry 3D: NVIDIA Quadro 410, AMD FirePro TM V3900, NVIDIA Quadro 6 Mid-range 3D: NVIDIA Quadro 410, AMD FirePro TM V7900, NVIDIA Quadro 6 Mid-range 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 MIGH-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro Motor 410, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 3D: NVIDIA Quadro 4000, AMD FirePro TM V7900, NVIDIA Quadro 6 Migh-rend 4D: NVIDIA Quadro 4D: NVIDIA Quadro 6 Mi	SATA 3 Gb/s controller, RAI , 1, 5, 10 capable	K rpm SATA drives: 300 GB SFF FF, 3.6 TB max; Up to (5) 3.5-in	F, 1.5 TB max; Up to (6) 2.5-inch ich 15K rpm SAS drives: 300,	
controller, RAID O, 1, 10 capable; Optional LSI 9260-8i 8-port 6 Gb/s SAS HW RAID Storage ^{6,7} Up to (5) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2 TB; Up to (4) 3 TB, 14 TE 10K rpm SATA drives: 250, 500, 1000 GB SFF, 6 TB max; Up to (6) 2.5-inch 10K rpm 450, 600 GB, 3 TB max; Up to (6) 2.5-inch SATA solid state drives: 128, 160, 256, 3 Up to (1) 3.5-inch SATA SED hard drive: 500 GB, 500 GB max Optical Storage ^{8,9} DVD-ROM, DVD+/-RW Super-Multi and Slot-Load, Blu-ray Writer Drive Bays Expansion Slots Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen3 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹o Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 Entry 3D: NVIDIA Quadro 410, AMD FirePro™ V3900, NVIDIA Quadro 6 Mid-range 3D: NVIDIA Quadro 2000, AMD FirePro™ V7900, NVIDIA Quadro Audio Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speake Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NI Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head	, 1, 5, 10 capable	K rpm SATA drives: 300 GB SFF FF, 3.6 TB max; Up to (5) 3.5-in	F, 1.5 TB max; Up to (6) 2.5-inch Ich 15K rpm SAS drives: 300,	
10K rpm SATA drives: 250, 500, 1000 GB SFF, 6 TB max; Up to (6) 2.5-inch 10K rpm 450, 600 GB, 3 TB max; Up to (6) 2.5-inch SATA solid state drives: 128, 160, 256, 3 Up to (1) 3.5-inch SATA SED hard drive: 500 GB, 500 GB max Optical Storage ^{8,9} DVD-ROM, DVD+/-RW Super-Multi and Slot-Load, Blu-ray Writer Drive Bays 3 external 5.25-inch bays, 4 internal 3.5-inch bays Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹⁰ Professional 2D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 Entry 3D: NVIDIA Quadro 410, AMD FirePro™3900, NVIDIA Quadro 6 NVIDIA Quadro 2000, AMD FirePro™ V7900, NVIDIA Quadro 6 NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro Adount of NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro Sound Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speake Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NIPorts Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head	controller, RAID 0, 1, 10 capable; Optional LSI 9260-8i 8-port 6 Gb/s SAS HW RAID 0, 1, 5, 10 capable Up to (5) 3.5-inch 7200 rpm SATA drives: 250, 500 GB, 1, 2 TB; Up to (4) 3 TB, 14 TB max; Up to (5) 2.5-inch 10K rpm SATA drives: 300 GB SFF, 1.5 TB max; Up to (6) 2.5-inch			
Drive Bays 3 external 5.25-inch bays, 4 internal 3.5-inch bays Expansion Slots 2 PCI Express Gen3 x16; 1 PCI Express Gen3 x16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹⁰ Professional 2D: Entry 3D: NVIDIA NVS 300, NVIDIA NVS 310, NVIDIA Quadro NVS 450 NVIDIA Quadro 410, AMD FirePro™ y5900, NVIDIA Quadro 6 NVIDIA Quadro 2000, AMD FirePro™ y5900 NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro NVIDIA Quadro 4000, MD FirePro™ V7900, NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA QUADRO 6000, AMD FirePro™ V7900, AMD FirePro™ V7900, AMD FirePro™ V7900,	AS drives: 300, 600 GB SI			
Expansion Slots 2 PCI Express Gen3 x 16; 1 PCI Express Gen3 x 16 (Available only with 2nd CPU); 1 PCI electrical; 1 PCI Express Gen2 x 8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹⁰ Professional 2D: Entry 3D: Mid-range 3D: NVIDIA Quadro 410, AMD FirePro™ y3900, NVIDIA Quadro 6 NVIDIA Quadro 2000, AMD FirePro™ y5900 High-end 3D: NVIDIA Quadro 4000, AMD FirePro™ y7900, NVIDIA Quadro Audio Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speake Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NI Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head				
electrical; 1 PCI Express Gen2 x8 mechanical/x4 electrical; 1 Legacy PCI Available Graphics¹⁰ Professional 2D: Entry 3D: Mid-range 3D: High-end 3D: NVIDIA Quadro 410, AMD FirePro™ V5900 NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro Audio Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speake Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NI Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head				
Entry 3D: NVIDIA Quadro 410, AMD FirePro™ V3900, NVIDIA Quadro 6 Mid-range 3D: NVIDIA Quadro 2000, AMD FirePro™ V5900 High-end 3D: NVIDIA Quadro 4000, AMD FirePro™ V7900, NVIDIA Quadro Audio Integrated Intel/Realtek HD ALC262 Audio, optional HP Thin USB Powered Speake Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NI Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head	xpress Gen3 x16 mechani	ical/x8 electrical; 1 PCI Express	Gen3 x8 mechanical/x4	
Network Dual integrated Intel GbE LAN; Infineon TPM 1.2 Controller; Optional Broadcom NI Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head	•	00, NVIDIA Quadro 6000, NVID	IA Tesla C2075 ¹¹	
Ports Front: 2 USB 3.0, 1 USB 2.0, 1 IEEE 1394a standard, 1 microphone in, 1 head	S			
	; Optional Intel NIC			
Internal: 6 USB 2.0 ports available by three 2x5 headers			I	
Input Devices HP PS/2 standard keyboard, HP USB standard keyboard, HP USB Smart Card Keybo 3-button optical mouse, USB SpaceExplorer, USB SpacePilot, USB Laser Mouse	ne m, 2 r 3/2, 2 NJ-43 t0 II	mouse, HP USB 2-button optic	al scroll mouse, HP USB	
Dimensions (H x W x D) 17.5 x 8.0 x 20.7 in (44.4 x 20.3 x 52.5 cm)				
Power Supply 850W 88% Efficient wide-ranging, active Power Factor Correction or 1125W 90%				
Compatible Displays (screen size diagonally measured) HP DreamColor LP2480zx Professional Display (24-inch diagonal widescreen), HF ZR2440w 24-inch LED Backlit IPS Monitor, HP LP2475w 24-inch Widescreen LC Backlit IPS Monitor	rd, HP PS/2 optical scroll	tive Power Factor Correction		
Warranty ¹² Limited three-year Mon-Fri 8-5 next business day, parts, labor and 24x7 phone su	rd, HP PS/2 optical scroll fficient wide-ranging, act ZR30w 30-inch S-IPS LCD	Monitor, HP ZR2740w 27-inch	n LED Backlit IPS Monitor, or, HP ZR2040w 20-inch LED	

Screen images courtesy of Autodesk.

- 1 Multi-Core technologies are designed to improve performance of multithreaded software products and hardware-aware multitasking operating systems and may require appropriate operating system software for full benefits; Not all customers or software applications will necessarily benefit from use of these technologies.
- 64-bit computing on Intel" architecture requires a computer system with a processor, chipset, BIOS, operating system, device drivers and applications enabled for Intel" 64 architecture. Processors will not operate (including 32-bit operation) without an Intel" 64 architecture-enabled BIOS. Performance will vary depending on your hardware and software configurations. See intel-com/info/em64t for more information.
 Intel's numbering is not a measurement of higher performance.
- The specifications shown in this column represent the following: (all core maximum turbo steps, one core maximum turbo steps). Turbo boost stepping occurs in 100MHz increments. Processors that do not have turbo functionality are denoted as N/A. Intel® Turbo Boost technology requires a PC with a processor with Intel® Turbo Boost capability. Intel® Turbo Boost performance varies depending on hardware, software, and overall system configuration.

Please visit intel.com/technology/turboboost for more information.

- Each processor supports up to 4 channels of DDR3 memory. To realize full performance at least 1 DIMM must be inserted into each channel.
- 6 SATA hardware RAID is not supported on Linux systems. The Linux kernel, with built-in software RAID, provides excellent functionality and performance. It is a good alternative to hardware-based RAID. Please visit h20000.www2.hp.com/bc/docs/support/SupportManual/c00060684/c00060684.pdf for RAID capabilities with Linux
- 7 For hard drives, 1 GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less.
- 8 Actual speeds may vary. Does not permit copying of commercially available DVD movies or other copyright protected materials. Intended for creation and storage of your original material and other lawful uses. Note that DVD-RAM cannot read or write to 2.6 GB Single Sided/5.2 GB Double Sided Version 1.0 media.
- 9 As Blu-ray contains new technologies, certain disc, digital connection, compatibility and/or performance issues may arise, and do not constitute defects in the product. Flawless playback on all systems is not guaranteed. In order for some Blu-ray titles to play, they may require a DVI or HDMI digital connection and your display may require HDCP support. HD DVD movies cannot be played on this workstation.
- 10 AMD Graphics are not supported when there are greater than 32 GB of system memory present.
- 11 NVIDIA Tesla C2075 requires the 1125W power supply.
- 12 HP Care Pack Services extend service contracts beyond the standard warranties. Service starts from date of hardware purchase. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at hp.com/go/lookuptool. Additional HP Care Pack Services information by product is available at hp.com/go/carepack. Service levels and response times for HP Care Packs may vary depending on your geographic location.

Learn more

hp.com/go/z820

© 2012 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Intel, Xeon, Core and vPro are trademarks of Intel Corporation in the U.S. and other countries. Windows is a U.S. registered trademark of Microsoft Corporation. AMD is a trademark of Advanced Micro Devices, Inc.

